



פס תאורת לד ליניארי במידות קומפקטיות. נצילות ושטף אור גבוהים במיוחד. יעילות אורית של 100Lm/W, התקנה קלה ונוחה. להארת מסדרונות ומבואות, תאורה נסתרת, תאורת מדפים, ארונות ואווירה.

מק"ט - 10583610

דגם - 4058075000360

קישור לדף מוצר ואביזרים נלווים באתר



5Years
Guarantee



PRO

220-240V
50-60Hz



IP20



IK03

מתאים לרשימות
התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Width	24mm
Length	573mm
Height	36mm
Product weight	300g

MATERIALS & COLORS

מבנה וגימור

Product color	white
Body material	PC
Protection class IEC 62262	IK03
Cover finishing	milky
Cover material	PC
Lens material	PC



ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	10W
Nominal current	0.13A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Driver output current	110mA
Dimmable driver mode	No
Power factor	>0.50
Inrush current	10A
Inrush current time T _{h50}	150µs
Max. no. of lum. On circuit break. B16 A	60
Max. no. of lum. On circuit break. C10 A	48
Max. no. of lum. On circuit break. C16 A	76

APPLICATION & MOUNTING

יישומים

Application environment	INDOOR
Mounting type	Surface
Mounting location	Ceiling/Wall-mounted
Type of protection	IP20
Ambient temperature range	-20...+40°C

CERTIFICATES & STANDARDS

תקנים

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=25°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62471 RG0 (Exempt) IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
IP 60529	IP20
Protection class IK (shock resistance)	IK03
Green Building	ISO 14001
ISO 9001	√

PERFORMANCE

ביצועים

Lifespan (Hr)	30000Hrs
Lifespan L70	>50000Hrs
Lifespan L80	>40000Hrs
Lifespan L90	>30000Hrs



PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	100Lm/W
Luminous flux	1000Lm
CCT	3000K
CRI	>80
LED manufacturer	Bridgelux
Chip type	SMD 2835
Beam angle	140°
CIE class	Semi-Direct
Efficiency	100%