




סדרת גופי תאורה צמודי תקרה דקים במיוחד במגוון גדלים והספקים. יעילות אורית גבוהה במיוחד 120Lm/W, דרייבר איכותי ללא ריצוד וכיסוי פרוסט מונע סנוור. התקנה קלה ונוחה. להתקנה בחדרי מגורים, משרדים, שטחים מסחריים, מבואות ועוד.

מק"ט - 17830007
דגם - LV960 BLACK
קישור לדף מוצר ואביזרים נלווים באתר



3Years Guarantee | 220-240V 50-60Hz | IP40 | מתאים לרשימת התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Width	600mm
Length	960mm
Product weight	5750g

MATERIALS & COLORS

מבנה וגימור

Product color	black
Body material	ABS
Protection class IEC 62262	IK08
Cover finishing	milky
Cover material	PC



ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	64W
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated

CERTIFICATES & STANDARDS

תקנים

Nisko Class	ECO 3 Years
Israeli Standard	Ta=45°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
CE	IEC 60598-1 IEC 60598-2-1 IEC 62493
Photobiological Safety	IEC 62471 RG0 (Exempt) IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP40
Protection class IK (shock resistance)	IK08

APPLICATION & MOUNTING

יישומים

Application environment	INDOOR
Mounting type	Surface
Mounting location	Ceiling
Type of protection	IP40
Ambient temperature range	0...+35°C

PERFORMANCE

ביצועים

Lifespan (Hr)	30000Hrs
---------------	----------



PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	120Lm/W
Luminous flux	7680Lm
CCT	3000/4000/6000K
CRI	>80
LED manufacturer	LVMING
Chip type	SMD 2835
Beam angle	120°
Efficiency	100%