


סדרת גופי תאורה הרמטיים עם נוכחות מרשימה ביעילות אורית גבוהה של כ- 110lm/W. פיזור אור אחיד, יעיל וחسכוני בחשמל. דרגת אטימות IP65. התקנה קלה באמצעות זוג תופסני נירוסטה חיצוניים לשמירה על אטימות הגוף. לשימוש ביתי במרפסת שמש, פרגולות, סוכות, מחסנים ביתיים ועוד.

מק"ט - 70337480
דגם - SY-8348W-B-12
קישור לדף מוצר ואביזרים נלווים באתר



3Years Guarantee | VALUE | 170-250V 50-60Hz | IP65 | מתאים לדרשות התקן הישראלי



DIMENSIONS & WEIGHT	מידות ומשקל
Width	116mm
Length	1215mm
Height	60mm
Product weight	790g

MATERIALS & COLORS	מבנה וגימור
Product color	white
Body material	PC
Cover finishing	milky
Cover material	PC



ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	80W
Nominal current	0.35A
Nominal voltage	170-250V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Driver output current	250mA
Dimmable driver mode	No

CERTIFICATES & STANDARDS

תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=25°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP65
ISO 9001	√

APPLICATION & MOUNTING

יישומים

Application environment	INDOOR
Mounting type	Surface
Mounting location	Ceiling/Wall-mounted
Type of protection	IP65
Ambient temperature range	0...+30°C

PERFORMANCE

ביצועים

Lifespan (Hr)	30000Hrs
---------------	----------

PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	103Lm/W
Luminous flux	8250Lm
CCT	4000K
CRI	>80
LED manufacturer	WEI ZHI PHOTOELECTRIC
Chip type	SMD 2835
Beam angle	120°
Efficiency	100%