




סדרת גופי תאורת מראה בעיצוב יוקרתי ובדרגת אטימות IP44. כוללים לדים איכותיים מבית LUMILEDS ודרייבר מוביל מבית TRIDONIC. להתקנה נוחה ומהירה בחדרי אמבטיה, מעל המראות ועוד.

מק"ט - 70338022
דגם - 23113
קישור לדף מוצר ואביזרים נלווים באתר



5Years Guarantee | PRO | 220-240V 50-60Hz | IP44 | IK04 | מתאים לרשימות התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Width	85mm
Length	895mm
Height	110mm
Product weight	2770g

MATERIALS & COLORS

מבנה וגימור

Product color	black
Body material	aluminum
Protection class IEC 62262	IK04
Cover finishing	Clear
Cover material	PMMA
Lens material	PMMA



ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	30W
Nominal current	0.14A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	TRIDONIC
Driver model	LC 38/400-700/54 Flex Ip SNC4
Driver output current	400-700mA
Dimmable driver mode	No
Power factor	>0.95
THDi	<15%
Output ripple current	≤5%
Inrush current	15A
Inrush current time T _{h50}	100µs
Max. no. of lum. On circuit break. B10 A	37
Max. no. of lum. On circuit break. B16 A	59
Max. no. of lum. On circuit break. C10 A	37
Max. no. of lum. On circuit break. C16 A	59

APPLICATION & MOUNTING

יישומים

Application environment	INDOOR
Mounting type	Surface
Mounting location	Wall-mounted
Type of protection	IP44
Ambient temperature range	-10...+40°C

CERTIFICATES & STANDARDS

תקנים

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-5 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62384 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP44
Protection class IK (shock resistance)	IK04

PERFORMANCE

ביצועים

Lifespan (Hr)	90000Hrs
Driver lifespan	90000Hrs



PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	42Lm/W
Luminous flux	1250Lm
CCT	3000K
CRI	>90
LED manufacturer	LUMILEDS
Chip type	SMD 2835
Beam angle	120°
Efficiency	100%