



גוף תאורה מתכוונן לצד מיטה בעיצוב קלאסי. כיסוי פריזמטי למניעת סנוור ופיזור אור אחיד. רכיבים איכותיים של חברות מובילות בעולם.

מק"ט - 70338034

דגם - 58034

קישור לדף מוצר ואביזרים נלווים באתר



3Years
Guarantee




VALUE

220-240V
50-60Hz



IP20

מתאים לרשימות
התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Width	60mm
Length	108mm
Diameter	80mm

MATERIALS & COLORS

מבנה וגימור

Product color	white
Body material	aluminum
Cover finishing	Prismatic

ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	3.6W
Nominal current	0.04A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	LIFUD
Driver model	LF-GIR003YS0300H(D)
Driver output current	300mA
Dimmable driver mode	No
Output ripple current	≤0.9%
Inrush current	30A
Inrush current time T_{h50}	100μs
Max. no. of lum. On circuit break. B10 A	38
Max. no. of lum. On circuit break. B16 A	60
Max. no. of lum. On circuit break. C10 A	64
Max. no. of lum. On circuit break. C16 A	102

APPLICATION & MOUNTING

יישומים

Application environment	INDOOR
Mounting type	Surface
Mounting location	Wall
Type of protection	IP20
Ambient temperature range	0...+50°C

CERTIFICATES & STANDARDS

תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=50°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
IP 60529	IP20

PERFORMANCE

ביצועים

Lifespan (Hr)	50000Hrs
Driver lifespan	50000Hrs



PHOTOMETRIC DATA	אופטיקה
Luminous efficacy	56Lm/W
Luminous flux	200Lm
CCT	3000K
CRI	>90
LED manufacturer	CREE
Chip type	COB
Beam angle	45°
Efficiency	100%