

גוף תאורת לד ליניארי הרמטי IP65. יעילות אורית גבוהה במיוחד 110Lm/w. גוף הניתן לפתיחה ולהזנה מחלקו האחורי. סגירה באמצעות תופסני נירוסטה ייעודיים. להתקנה בחניונים, מחסנים, מבני תעשייה, מפעלים, מוסכים ועוד.


מק"ט - 71333341

דגם - LG07J-12-33-5.7K

קישור לדף מוצר ואביזרים נלווים באתר



5 YEAR GUARANTEE | PRO | 220-240V 50-60Hz | IP65 | IK08 | מתאים לרשימת התקן הישראלי ✓



## DIMENSIONS & WEIGHT

## מידות ומשקל

Width	79mm
Length	1205mm
Height	68mm
Product weight	1350g

## MATERIALS & COLORS

## מבנה וגימור

Product color	gray
Body material	PC
Protection class IEC 62262	IK08
Cover finishing	milky
Cover material	PC

## ELECTRICAL DATA

## נתונים חשמליים

Nominal wattage	33W
Nominal current	0.15A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	HOWLONGER
Driver model	LSN40W024T2
Driver output current	240mA
Dimmable driver mode	No
Power factor	>0.97
THDi	<6%
Output ripple current	≤5%
Inrush current	24.6A
Inrush current time $T_{h50}$	204μs
Max. no. of lum. On circuit break. B10 A	67
Max. no. of lum. On circuit break. B16 A	83
Max. no. of lum. On circuit break. C10 A	70
Max. no. of lum. On circuit break. C16 A	112

## APPLICATION & MOUNTING

## יישומים

Application environment	Indoor Outdoor
Mounting type	Surface
Mounting location	Ceiling Wall
Type of protection	IP65
Ambient temperature range	-20...+40°C

## CERTIFICATES & STANDARDS

## תקנים

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
International Standards	ENEC
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
TM21	√ Ta=35°C
IP 60529	IP65
Protection class IK 62262 (shock resistance)	IK08
Green Building	ISO 14001
ISO 9001	√
אישורים נוספים	√ פיקוד העורף √ מבחן הרס ת"י 5103-4

## PERFORMANCE

## ביצועים

Lifespan (Hr)	75000Hrs
TM21	√ Ta=35°C
Lifespan L70	>60000Hrs
Lifespan L80	>60000Hrs
Lifespan L90	>43000Hrs
Driver lifespan	75000Hrs

## PHOTOMETRIC DATA

## אופטיקה

Luminous efficacy	120Lm/W
Luminous flux	3950Lm
CCT	5700K
CRI	>80
LED manufacturer	EVERLIGHT
Chip type	SMD 2835
Beam angle	120°
CIE class	Direct
Efficiency	100%