





סדרת גופי תאורת לד צמודי קיר 12V בדרגת אטימות IP65. עיצוב דק, חדיש וקומפקטי. כולל שיטה ייחודית לבחירת גוון אור על ידי לחיצת כפתור. חסכוני בצריכת חשמל ותחזוקה. להתקנה על חומות, מעברים, כניסות לחניונים ועוד.


מק"ט - 71461301

דגם - 2004-12V 2W BLACK

קישור לדף מוצר ואביזרים נלווים באתר



2Years Guarantee | VALUE | 12V AC/DC | III | IP65 | מתאים לדרשות התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Width	230mm
Length	28mm
Height	80mm

MATERIALS & COLORS

מבנה וגימור

Product color	black
Body material	PC
Cover finishing	milky
Cover material	PC



ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	2W
Nominal current	0.26A
Nominal voltage	12DCV
Mains frequency	50/60Hz
Protection class	Class 3
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Dimmable driver mode	No

CERTIFICATES & STANDARDS

תקנים

Nisko Class	VALUE 2 Years
Israeli Standard	Ta=25°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP65

APPLICATION & MOUNTING

יישומים

Application environment	OUTDOOR
Mounting type	Surface
Mounting location	Wall
Type of protection	IP65
Ambient temperature range	-20...+40°C

PERFORMANCE

ביצועים

Lifespan (Hr)	20000Hrs
---------------	----------

PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	100Lm/W
Luminous flux	200Lm
CCT	3000/4000/6500K
CRI	>80
LED manufacturer	OSRAM
Chip type	SMD 2835
Beam angle	70°
Efficiency	100%