




מנורת תלייה דקורטיבית במגוון צבעים ובעיצוב מודרני מסדרת SATURN. מיוצרת מחומרים איכותיים וברמת גימור גבוהה. איכות אורית גבוהה  $CRI > 90$ , זווית הארה  $51^\circ$  וכיסוי אופטי פריזמטי. להארה בבתי מגורים, לובאים, אולמות אירועים, בתי מלון ועוד.




מק"ט - 75410619

דגם - UNI-C-501-WG-3K

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IP20
- CLASS1
- 220-240 וולט 50-60 הרץ
- 3 שנות אחריות



## DIMENSIONS & WEIGHT

Height	82mm
Diameter	220mm
Product weight	780g

## MATERIALS & COLORS

Cable surface [mm <sup>2</sup> ]	White/gold
Protection class IEC 62262	aluminum
Cover material	Clear

## ELECTRICAL DATA

Cable length	2
Nominal wattage	5W
Nominal current	0.04A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	EAGLERISE
Driver model	LS-6-300 SB
Driver output current	300mA
Dimmable driver mode	No

## CERTIFICATES & STANDARDS

Nisko Class	ECO 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20
ISO 9001	✓

## APPLICATION & MOUNTING

Ambient temperature range 0...+35°C

---

## PHOTOMETRIC DATA

Luminous efficacy	60Lm/W
Luminous flux	300Lm
CCT	3000K
CRI	>90
Beam angle	51°
CIE class	Direct
Efficiency	100%