


מנורת תלייה דקורטיבית מסדרת LUNARA בעיצוב מודרני. מיצרת מחומרים איכותיים, מגוון צבעים ואורכים ורמת גימור גבוהה. איכות אורית גבוהה - CRI>90. ייעודית לבתי מגורים, לובאים, אולמות אירועים, בתי מלון ועוד.

מק"ט - 75410640
 דגם - UNI-ICS-0033-B
 קישור לדף מוצר ואביזרים נלווים באתר



3 YEAR GUARANTEE | IP20 | מתאים לרשימת התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Height	118mm
Diameter	250mm
Product weight	530g

MATERIALS & COLORS

מבנה וגימור

Product color	black
Body material	aluminum
Cover finishing	milky
Cover material	PC

ELECTRICAL DATA

נתונים חשמליים

Cable length	1.4
Nominal wattage	12W
Nominal current	0.06A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	External LED driver
Driver manufacturer	EAGLERISE
Driver model	LS-12-300 LI EXC
Driver output current	300mA
Dimmable driver mode	No
Power factor	>0.93

APPLICATION & MOUNTING

יישומים

Application environment	Indoor
Mounting type	Suspension
Mounting location	Ceiling
Type of protection	IP20
Ambient temperature range	0...+35°C

PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	50Lm/W
Luminous flux	600Lm
CCT	3000K
CRI	>90
LED manufacturer	OSRAM
Chip type	SMD 2835
Beam angle	115°
CIE class	Direct
Efficiency	100%

CERTIFICATES & STANDARDS

תקנים

Nisko Class	ECO 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20
ISO 9001	√

PERFORMANCE

ביצועים

Lifespan (Hr)	100000Hrs
---------------	-----------