





צילינדר מבית SYLVANIA העולמית. מיוצר מחומרים איכותיים ובדרגת אטימות וחוזק מכני גבוהים - IP65, IK08. עיצוב אלגנטי, מתאים להתקנה במגוון גבהים. להארת מבואות, מרפסות, משטחים אופקיים ועוד.


מק"ט - 75501213

דגם - ZB502FS

קישור לדף מוצר ואביזרים נלווים באתר



5Years Guarantee | PRO | 220-240V 50-60Hz | IP65 | IK08 | מתאים לדרגות התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Height	138mm
Diameter	126mm
Product weight	1600g

MATERIALS & COLORS

מבנה וגימור

Product color	white
Body material	aluminum
Protection class IEC 62262	IK08
Cover finishing	Clear
Cover material	PC

ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	11W
Nominal current	0.05A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	EAGLERISE
Driver model	EBP012C0250CHP
Driver output current	250mA
Dimmable driver mode	No
Power factor	>0.92
Inrush current	10A

CERTIFICATES & STANDARDS

תקנים

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
TM21	√ Ta=35°C
LM79	√
IP 60529	IP65
Protection class IK (shock resistance)	IK08
Green Building	√
ISO 9001	√

APPLICATION & MOUNTING

יישומים

Application environment	OUTDOOR
Mounting type	Surface
Mounting location	Ceiling
Type of protection	IP65
Ambient temperature range	-30...+35°C

PERFORMANCE

ביצועים

Lifespan (Hr)	54000Hrs
TM21	√ Ta=35°C
Lifespan L70	>54000Hrs
Lifespan L80	>54000Hrs
Driver lifespan	43800Hrs



PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	73Lm/W
Luminous flux	800Lm
CCT	3000K
CRI	>80
LED manufacturer	CREE
Chip type	COB
Beam angle	83°
CIE class	Direct
Efficiency	100%