





צילינדר מבית SYLVANIA העולמית. מיוצר מחומרים איכותיים ובדרגת אטימות וחוזק מכני גבוהים - IP65, IK08. עיצוב אלגנטי, מתאים להתקנה במגוון גבהים. להארת מבואות, מרפסות, משטחים אופקיים ועוד.


מק"ט - 75504004

דגם - ZB502FM

קישור לדף מוצר ואביזרים נלווים באתר



5Years Guarantee | PRO | 220-240V 50-60Hz | IP65 | IK08 | מתאים לדרגות התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Height	150mm
Diameter	168mm
Product weight	2700g

MATERIALS & COLORS

מבנה וגימור

Product color	black
Body material	aluminum
Protection class IEC 62262	IK08
Cover finishing	Clear
Cover material	PC

ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	38W
Nominal current	0.18A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	GALOPPATO
Driver model	GLP40WR900-P
Driver output current	900mA
Dimmable driver mode	No
Power factor	>0.91

CERTIFICATES & STANDARDS

תקנים

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
TM21	√ Ta=35°C
IP 60529	IP65
Protection class IK (shock resistance)	IK08
Green Building	√
ISO 9001	√

APPLICATION & MOUNTING

יישומים

Application environment	OUTDOOR
Mounting type	Surface
Mounting location	Ceiling
Type of protection	IP65
Ambient temperature range	-30...+35°C

PERFORMANCE

ביצועים

Lifespan (Hr)	54000Hrs
TM21	√ Ta=35°C
Lifespan L70	>60000Hrs
Lifespan L80	>51000Hrs



PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	84Lm/W
Luminous flux	3200Lm
CCT	4000K
CRI	>80
LED manufacturer	CREE
Chip type	COB
Beam angle	93°
CIE class	Direct
Efficiency	100%