



צמודי קיר לד DOWN בעיצוב אלגנטי לתאורת חוץ. הארה כלפי מטה, חוזק מכני IK08 ודרגת אטימות IP65. יעילות אורית גבוהה, להבטחת חיסכון בצריכת החשמל. תוצרת SYLVANIA העולמית. להארת היקפי מבנה, חזיתות מבנים, עמודים, חומות, מרפסות ועוד.

מק"ט - 75522013

דגם - ZB703FM

קישור לדף מוצר ואביזרים נלווים באתר



5Years
Guarantee



PRO



220-240V
50-60Hz



IP65

IK08

מתאים לדרשות
התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Width	168mm
Height	204mm
Diameter	144mm
Product weight	2700g

MATERIALS & COLORS

מבנה וגימור

Product color	white
Body material	aluminum
Protection class IEC 62262	IK08
Cover finishing	Clear
Cover material	PC

ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	18W
Nominal current	0.09A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	EAGLERISE
Driver model	EBP018C0450CHP
Driver output current	450mA
Dimmable driver mode	No
Power factor	>0.90
Inrush current	10A

CERTIFICATES & STANDARDS

תקנים

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
TM21	√ Ta=35°C
IP 60529	IP65
Protection class IK (shock resistance)	IK08
Green Building	√
ISO 9001	√

APPLICATION & MOUNTING

יישומים

Application environment	OUTDOOR
Mounting type	Surface
Mounting location	Wall
Type of protection	IP65
Ambient temperature range	-30...+35°C

PERFORMANCE

ביצועים

Lifespan (Hr)	54000Hrs
TM21	√ Ta=35°C
Lifespan L70	>54000Hrs
Lifespan L80	>54000Hrs
Lifespan L90	>54000Hrs
Driver lifespan	43800Hrs



PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	94Lm/W
Luminous flux	1700Lm
CCT	3000K
CRI	>80
LED manufacturer	CREE
Chip type	COB
Beam angle	89°
Efficiency	100%