


סדרת ספוטס מתכוננים למערכת פס צבירה חד פאזי אוניברסלי, בעיצוב קלאסי ונקי. תאורה מדויקת, טבעית ואיכותית, מקדם מסירת צבע גבוה $CRI > 90$ וללא ריצוד. 3 גווי אור בגוף אחד - חם, ניטרלי או קר. להארה בבתי, מוזיאונים, משרדים, חנויות, חלונות ראווה ועוד.

מק"ט - 77491115

דגם - PHASE TRACK LIGHT 12W 3CCT 38D BLACK-1 9412

קישור לדף מוצר ואביזרים נלווים באתר



3Years
Guarantee



VALUE

220-240V
50-60Hz



IP20

מתאים לרשימות
התקן הישראלי



DIMENSIONS & WEIGHT

Length	115mm
Diameter	60mm
Product weight	240g

מידות ומשקל

MATERIALS & COLORS

Product color	black
Body material	aluminum
Cover finishing	Semi-Transparent
Cover material	PC
Lens material	PMMA

מבנה וגימור

ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	12W
Nominal current	0.05A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Dimmable driver mode	No
Power factor	>0.94

CERTIFICATES & STANDARDS

תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20
ISO 9001	√

APPLICATION & MOUNTING

יישומים

Application environment	INDOOR
Mounting type	Trackline
Mounting location	Ceiling
Type of protection	IP20
Ambient temperature range	-10...+35°C

PERFORMANCE

ביצועים

Lifespan (Hr)	30000Hrs
---------------	----------

PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	92Lm/W
Luminous flux	1100(4K)Lm
CCT	3000/4000/6000K
CRI	>90
LED manufacturer	TYF
Chip type	SMD 2835
Beam angle	38°
CIE class	Direct
Efficiency	100%