




תאורת הצפה לינארית מקצועית ביעילות אורית גבוהה 150Lm/w ושטף אורי מיטבי. פתרונות הארה מושלמים בגבהים של 3-14 מטרים ובדרגת אטימות IP65. להתקנה בתלייה באמצעות סט ייעודי או כגוף צמוד באמצעות אביזר מתכוונן. פתרון אידיאלי עבור מפעלים, מחסנים, מרכזי ליקוט והפצה, חנויות ועוד.

מק"ט - 77855040

דגם - K60241

קישור לדף מוצר ואביזרים נלווים באתר



5Years
Guarantee



PRO


220-240V
50-60Hz



IP65

IK09

מתאים לדרשות
התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Width	129mm
Length	365mm
Height	100mm
Product weight	3500g

MATERIALS & COLORS

מבנה וגימור

Product color	black
Body material	aluminum
Protection class IEC 62262	IK09
Cover finishing	milky
Cover material	PC
Lens material	PC

ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	55W
Nominal current	0.24A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	SOSEN
Driver model	SS-65GA-56B
Driver output current	2400mA
Dimmable driver mode	1-10V DALI
Power factor	>0.97
THDi	<12%
Output ripple current	≤5%
Inrush current	45A
Inrush current time T_{h50}	200μs
Max. no. of lum. On circuit break. B10 A	9
Max. no. of lum. On circuit break. B16 A	14
Max. no. of lum. On circuit break. C10 A	15
Max. no. of lum. On circuit break. C16 A	24

APPLICATION & MOUNTING

יישומים

Application environment	INDOOR
Mounting type	Surface/Pendant
Mounting location	Ceiling
Type of protection	IP65
Ambient temperature range	-25...+40°C

CERTIFICATES & STANDARDS

תקנים

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
TM21	√ Ta=35°C
LM79	√
Binning	√ Declaration SDCM ≤ 5
IP 60529	IP65
Protection class IK (shock resistance)	IK09
Green Building	ISO 14001
ISO 9001	√

PERFORMANCE

ביצועים

Lifespan (Hr)	90000Hrs
TM21	√ Ta=35°C
Lifespan L70	>54000Hrs
Lifespan L80	>54000Hrs
Lifespan L90	>44000Hrs
Driver lifespan	90000Hrs



PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	142Lm/W
Luminous flux	7800Lm
CCT	4000K
CRI	>80
LED manufacturer	LUMILEDS
Chip type	SMD 2835
SDCM	≤5
Beam angle	90°
CIE class	Direct
Efficiency	100%